

# Troubleshooting

# Troubleshooting

## ■ MM-1

症 状	原 因	处 置
No sound of OPT Out from MM-1.	POSITION setting is not D.	Select D from the POSTION in the menu.
No picture from AV of the Picture In.	No (-) signal input to the PARKING on the Smart Interface.	Connect (-) signal input cable to the PARKING.
	Input is in CAMERA of the Picture In instead of AV.	Connect the input to AV correctly.
The picture is unclear or distorted.	There is a noise on the AV line.	Make sure the cable is connected correctly.
		Replace with a good quality cable.
Noise in Line output signal (analog)	Noise on the LINE output cable.	Make sure the cable is connected correctly.
No sound of LINE or OPT Out from auxiliary inputs.	POSITION setting is not correct.	Select the position correctly.
	Switch is not connected to REM-IN of Smart Interface.	Connect the switch correctly.
No sound (Power is on).	Proper music files are not downloaded on CF.	Refer to the MM-1 Owner's manual for downloading the music files to the CF.
	POSITION setting is not correct.	Select the position correctly.

## ■ Mirror Station + MM-1

症 状	原 因	处 置
VOL display of Mirror Station is not shown on MM-1.	No (-) signal is into the PARKING of Smart Interface.	Connect (-) signal cable to the PARKING.
	Power of the AZ is off.	Turn on the power by a remote control.
	The AV Out of AZ and the AV In of Smart Interface are not connected properly.	Make sure the wiring is connected properly.
Audio reproduces later than the picture when connecting DVD.	Because AZ process enormous data, the audio reproduces late. Make the crossover slope of each channel gradual.	Select None for subwoofer's hi-pass, -18dB for subwoofer's low-pass, -12dB for other channels' hi-pass, and -18dB for other channels' low-pass.
No sound from Mirror Station (MM-1 plays but no sound)	POSITION setting of MM-1 is not D.	Select D from the POSTION in the menu.
	OPT In is not connected properly.	Make sure the cable is connected correctly.
	MM-1 is not selected as the input source of AZ.	Select MM-1 for the input source.
	Digital cable is defective.	Unplug the digital cable and make sure of the OPT signal output.
	MUTE is set to each channel.	Cancel the MUTE settings. (All the channels are MUTE at initial setting.)
Power of Mirror Station does not turn on.	Wirings of +B, GND, and Remote In are not connected properly.	Make sure of the wiring.
	Enough power supply is not provided.	Take the +B line from different source.
	Remote Eye is installed to where it cannot detect the signal.	Reconsider the place to install the Remote Eye.
	Remote Eye is not connected properly.	Make sure of the Remote Eye connection.
2 VOL displays show on MM-1.	POSITION setting of MM-1 is not D.	Select D from the POSTION in the menu.
Remote signal of AZ is not output.	Remote Out of AZ outputs only when the input source is LINE or MINI.	This Remote Out of AZ is used only when using High Level Input of Smart Interface.
No picture	AV input and output of AZ are not connected properly.	Make sure the cable is connected correctly.
	No (-) signal is into the PARKING of Smart Interface.	Connect (-) signal cable to the PARKING.
Vol level of Mirror Station does not rise.	Remote Eye is not connected properly.	Make sure of the Remote Eye connection.
	Remote Eye is installed to where it cannot detect the signal.	Reconsider the place to install the Remote Eye.
	The battery of remote control is discharged.	Replace the battery.
Software fails to work.	The software is not installed properly.	Reinstall the software.
	USB cable is not connected properly.	Make sure the cable connection.
	Port is not selected properly.	Select a port at the Setting.